Drift Correction (glossary)

drift correction

The printable version is no longer supported and may have rendering errors. Please update your browser bookmarks and please use the default browser print function instead.

A resilience design principle that states that the drift of a system into a region of increasing risk should be monitored and appropriate responses should be formulated and executed - adapted from (Leveson et al. 2006)

In a resilience context according to Jackson and Ferris (2013) drift correction is a component principle of the adaptability grouping.

Sources

Leveson, N., N. Dulac, D. Zipkin, Cutcher-Gershenfeld, J. Carroll, and B. Barrett. 2006. "Engineering Resilience into a Safety-Critical System." In *Resilience Engineering: Concepts and Precepts*, edited by E. Hollnagel, D. D. Woods and N. Leveson. Aldershot, UK: Ashgate Publishing Limited.

Jackson, Scott, and Timothy Ferris. 2013. "Resilience Principles for Engineered Systems." Systems Engineering 16 (2):152-164.

Discussion

This is a key resilience design principle. Although the definition above implies a gradual drift into a high risk state, it can also be interpreted to imply an immediate impending danger as was done by (Jackson 2010).

Jackson, S. 2010. Architecting Resilient Systems: Accident Avoidance and Survival and Recovery from Disruptions. Edited by A. P. Sage, Wiley Series in Systems Engineering and Management. Hoboken, NJ, USA: John Wiley & Sons.

SEBoK v. 2.10, released 06 May 2024

Retrieved from

 $"https://sandbox.sebokwiki.org/index.php?title=Drift_Correction_(glossary) \& oldid=71564"$

This page was last edited on 2 May 2024, at 22:43.