

# Ellipsoidal Height or Geodetic Height (glossary)

---

ellipsoidal height or geodetic height

The printable version is no longer supported and may have rendering errors. Please update your browser bookmarks and please use the default browser print function instead.

*Ellipsoidal height, also known as geodetic height  $h$ , is the distance of a point from the reference ellipsoid along the perpendicular from the reference ellipsoid to this point, positive if upwards or outside of the reference ellipsoid.*

Notes to Entry:

1. Only used as part of a three-dimensional ellipsoidal coordinate system or as part of a three-dimensional Cartesian coordinate system in a three-dimensional projected coordinate reference system, but never on its own.
2. Ellipsoidal height and geodetic height are registered with the ISO as two separate terms, but in practice are frequently used synonymously.

## Sources

ISO TC211. "Ellipsoidal height." In: *ISO TC211 Multilingual Glossary*. Version from 2020-06-02. Concept ID: 2406. Available at: <https://isotc211.geolexica.org/concepts/2406/>.

## Discussion

None.

---

Retrieved from  
"https://sandbox.sebokwiki.org/index.php?title=Ellipsoidal\_Height\_or\_Geodetic\_Height\_(glossary)&oldid=69353"

---

**This page was last edited on 18 November 2023, at 21:56.**